

## HD+ Storage Expansion DAS

### Features:

Can Expand storage with up to 84TB for almost any LuxRiot HD NVR/DVR or Hybrid server. Both RAID5 or RAID6 configuration available. HOT SWAP Hard Drives. For RAID5 includes an extra HOT SPARE for better redundancy. Hot Swap redundant Power supplies. SAS Interface to connect to servers. Faster than NAS.

### Specifications

High performance SAS and high capacity SATA drives can be mix-matched in a single subsystem. The flexibility reduces Total Cost of Ownership (TCO)  
 Two 4-port connectors for host or expansion with automatic port speed detection and negotiation. redundant power supply and hot-swappable rear fans put maintenance and management at ease. The ultimate choice for a Fast External SATA-based expansion storage solution. Recommended up to 3 units in Daisy chain. 3U.



DAS PART#	External Direct attached storage Raid5.
LR-DAS-10TBR5+H	3U DAS <b>10TB</b> RAID5 with Hot spare and redundant Power supply.Total of 7 x 2TB drives.
LR-DAS-12TBR5+H	3U DAS <b>12TB</b> RAID5 with Hot spare and redundant Power supply.Total of 8 x 2TB drives.
LR-DAS-14TBR5+H	3U DAS <b>14TB</b> RAID5 with Hot spare and redundant Power supply.Total of 9 x 2TB drives.
LR-DAS-16TBR5+H	3U DAS <b>16TB</b> RAID5 with Hot spare and redundant Power supply.Total of 10 x 2TB drives.
LR-DAS-18TBR5+H	3U DAS <b>18TB</b> RAID5 with Hot spare and redundant Power supply.Total of 11 x 2TB drives.
LR-DAS-20TBR5+H	3U DAS <b>20TB</b> RAID5 with Hot spare and redundant Power supply.Total of 12 x 2TB drives.
LR-DAS-22TBR5+H	3U DAS <b>22TB</b> RAID5 with Hot spare and redundant Power supply.Total of 13 x 2TB drives.
LR-DAS-24TBR5+H	3U DAS <b>24TB</b> RAID5 with Hot spare and redundant Power supply.Total of 14 x 2TB drives.
LR-DAS-26TBR5+H	3U DAS <b>26TB</b> RAID5 with Hot spare and redundant Power supply.Total of 15x 2TB drives.
LR-DAS-28TBR5+H	3U DAS <b>28TB</b> RAID5 with Hot spare and redundant Power supply.Total of 16 x 2TB drives.

Host Interface: Single Mini SAS 4x connector  
Expansion Interface: Single Mini SAS 4x connector  
Drive Interface: 3Gb dual ported SAS, 1.5/3.0Gb single ported SATA  
Drive RPM: Up to 15,000  
Form Factor: 3.5", 1" height  
LED Indicators, Audible Alarm Yes  
Disk Drive: Hot-swap 16-bay  
Cooling: Hot-swap, Redundant 2+1  
Power Supplies: 500W 1+1 hot-swap redundant PFC  
Power Entry: Dual AC Inlet  
Universal A/C Input: 100~240V AC full range

Pictures and specifications are subject to change without prior notice